



## **SYCON 2702:** *The entry-level model for high demands*

- > for water softening plants
- > for reverse osmosis systems



Drinking water



Raw water



Waste water



Boiler water



Cooling water

*Safety reliably produced.*

# The titration device SYCON 2702

## Since 2012 ...

... our SYCON analyzers stand the test in the daily use. The SYCON 2702 is the entry-level model for high demands. It is a titration device which is able to monitor an adjustable limit value.

## It can be used ...

... where a process depends on the precise compliance with individual readings. With the SYCON 2702 we offer reliable analysis technology according to your requirements. The SYCON 2702 includes a demand-controlled regeneration of a softening unit. For this purpose, you choose the reagent with the appropriate measuring range from our extensive range of products. This is controlled in an adjustable time interval and if exceeded, a signal is passed to the controller.



## Advantages and highlights at a glance:

- 1** The display allows a quick and comprehensive metering of the device's status and shows the results of the last 100 measurements. Simplified operation via detailed, clear menu navigation. An installation wizard helps you during the initial startup.
- 2** In contrast to the SYCON 2602 limit value device, the SYCON 2702 allows to freely select the limit value to be measured in the range from 0.02 to 30 °dH. In addition, the measurement of the carbonate hardness is possible in the range from 0.3 to 9.0 °KH.
- 3** Cost-effective and easy exchange of the pump thanks to the new clip fixing at the drive.
- 4** Tool-free maintenance of the measuring chamber by installation of locking pins directly on the measuring chamber.
- 5** Our reagents are produced according to our own recipe and have a shelf-life of 24 months. They are optimally synchronized with the full- colour sensor.
- 6** The new colour-coded terminals facilitate the assignment and ensure a convenient connection of the cables. There are two additional terminals each with switched L- and N-conductors, which can be bridged to the relay contacts.
- +** On the inserted SD card, all measurement results are saved with a time stamp.

***Safety reliably produced.***

## Overview of performance features:

### Intelligent and accurate

The device does not need to be calibrated. Due to the integrated measuring technology and a two-stage analysis procedure with zero point measurement, external measuring influences due to contamination of the measuring chamber, turbidity of the sample and extraneous light influences are automatically detected and eliminated in the evaluation of the analysis. The maintenance-free full colour sensor is one of the key components for the autonomous operation of the device.

### Programmable limit value

Hardness breakthroughs are reliably detected by the reagent's colour reaction. You choose the reagent according to your degree of hardness. The limit value can be freely selected within the measuring range of 0.02 to 30 °dH.

### Analog interface

The measured value is shown on the display and can be emitted via the analog 4 to 20 mA interface.

### Very high accuracy

After a bad measurement, a reference measurement can be carried out to evaluate the result at intervals of 4 minutes. This prevents false alarms due to the negative ion effect.

### Multilingual menu

The menu navigation is switchable between German, English, French, Spanish, Italian, Russian, Polish, Dutch and Danish.

### Extensive alarm functions

If the measured value is exceeded, an alarm is emitted by switching a potential-free relay. This alarm output can be placed on a control room for signaling purposes, or used to operate a horn, to close a valve or to head for a program to regenerate a water softening unit.

### Diagnostic program

If you encounter technical problems with the device, a fault message is issued by switching a potential-free relay. The detailed diagnostic program guides you step by step through all functions in an easy to understand way. Thus, the device is roundly checked and the cause of the error message is clearly located.

### Digital input

The potential-free switch of a flow meter, a timer or any other state switch can be connected to this input. When the contact is open, no analyses are run in the programmed interval. Alternatively, this input can be used as start input for analyses.

### Two potential-free relay outputs

The SYCON 2702 has 2 relays. The first relay reports a measured value exceeded during the detection of hard water. Relay two indicates the readiness for operation or a fault on the device.





# The titration device SYCON 2702

## General Specifications

### Value / Range

Supply voltage	100 - 240 VAC at 50 - 60 Hz
Power consumption	25 VA (during operation)
IP-protection class	IP43 (with housing IP54)
Ambient temperature	5 - 45 °C
Temperature of water sample	5 - 40 °C
Humidity	20 - 90 % RH non-condensing

## Technical Data

### Value / Range

Installation	wall mounting in closed rooms
Dimensions	on wall holder: 274 x 275 x 130 mm (W x L x H) with housing: 330 x 300 x 185 mm (W x L x H)
Weight	on wall holder: 1,9 kg with housing: 3,7 kg
Relay outputs	2 relays, 250 VAC / VDC 4 A potential free outputs NC/NO > limit value alert > device error
Signal input	potential free input contact
Connection inlet / outlet	tubes with 6 mm outer diameter

## Analysis Features

### Value / Range

Measuring method	colorimetric		
Measuring range	<b>total hardness</b>	<b>carbonate hardness</b>	
	0.012 ... 30	0.3 ... 22.5	°dH
	0.015 ... 37.6	0.4 ... 28.2	°e
	0.021 ... 53.4	0.5 ... 40	°fH
	0.214 ... 534	5.34 ... 400	ppm
Reagent consumption	< 0.05 ml / analysis up to 10000 analyses per 500 ml bottle		
Shelf-life of reagents	24 months		
Water consumption	approx. 1000 ml / analysis, the water consumption depends on the inlet pressure and the flushing time		
Pressure of inlet water	approx. 0.5 ... 5 bar, use a pressure reducer in case of an inlet water pressure above 2 bar		
Water sample	clear, colour free, without any solids and gas bubbles pH 4 ... 10.5, iron < 3 ppm, copper < 0,2 ppm, aluminium < 0.1 ppm, manganese < 0.2 ppm, acid capacity KS4.3 < 5 mmol/l		

## Our product range:

### Water hardness measurement

With our analyzers of the SYCON series you can also monitor the function of your ion exchangers and reverse osmosis systems. For steam boiler houses we offer you an analyzer with approval for BoB operation. For each of your applications, you can obtain an optimized instrument with an individually configurable range of functions from RLS Wacon analytics.



### Sample coolers

You will find coolers in our assortment that allow you to take samples for manual analysis. We also offer pre-coolers for analytical instruments. Body and cooling coil are made of stainless steel (type 1.4571) and are approved for a nominal pressure up to 16 bar.



### Reagents

We can supply you with the right reagent for your analyzer. We will gladly send you an overview of the available reagents for your SYCON analyzer. In addition to the reagents of RLS Wacon analytics, our delivery program also includes compatible reagents for the analyzers of other manufacturers.



### Test sets

We offer a wide range of test sets for the determination of water parameters. Besides many common quick tests for the control of residual hardness, total hardness, chlorine content and iron concentration you will also find many test sets which are needed for niche applications.

The RLS Wacon analytics GmbH is a family-owned enterprise based in Hildesheim, Germany. For more than 40 years, we are developing and manufacturing robust and safe measurement and sensor technology for demanding applications. We hereby consistently focus on quality and well-known products. Our particular interest is the dialogue with customers, partners and suppliers. That's how **safety is reliably produced.**

Gropiusstr. 12, D-31137 Hildesheim  
Tel.: +49 (0) 5121 / 28126-0  
Fax: +49 (0) 5121 / 28126-20  
info@rls-wacon.de • www.rls-wacon.de

**RLS Wacon**  
analytics GmbH